





High-Speed Thermal Printer



Part Number		FTP-421MCL001, FTP-421DCL001	FTP-421MCL002, FTP-421DCL002
Figure			
Dot structure [dots/line]		320	320
Horizontal dot pitch [dots/mm (dpi)]		6 (152)	6 (152)
Printing speed [dot lines/s]		250	170
Dimensions W x D x H [mm (in.)]	Mechanism	110 x 60 x 40 (4.331 x 2.362 x 1.575)	110 x 60 x 40 (4.331 x 2.362 x 1.575)
	Interface board	140 x 89 x 19 (5.512 x 3.504 x 0.748)	140 x 89 x 19 (5.512 x 3.504 x 0.748)
Weight [g]	Mechanism	300	300
	Interface board	150	150
Power supply voltage [V]		24/5	24/5
Paper width [mm (in.)]		60 (2.362)	60 (2.362)
Remarks		1 ply paper type Centronics standard interface UL recognized	2 ply paper type Centronics standard interface UL recognized

High-Speed Thermal Printer



Part Number		FTP-421MCL002, FTP-421DCL004	FTP-421MCL001, FTP-421DSL001
Figure			
Dot structure [dots/line]		320	320
Horizontal dot pitch [dots/mm (dpi)]		6 (152)	6 (152)
Printing speed [dot lines/s]		250	214
Dimensions W x D x H [mm (in.)]	Mechanism	110 x 60 x 40 (4.331 x 2.362 x 1.575)	110 x 60 x 40 (4.331 x 2.362 x 1.575)
	Interface board	140 x 89 x 19 (5.512 x 3.504 x 0.748)	140 x 140 x 20 (5.512 x 5.512 x 0.787)
Weight [g]	Mechanism	300	300
	Interface board	150	160
Power supply voltage [V]		24/5	24/5/±12
Paper width [mm (in.)]		60 (2.362)	60 (2.362)
Remarks		Thick paper/label form type Centronics standard interface UL recognized	1 ply paper type RS-232C standard interface UL recognized

THERMAL PRINTERS

High-Speed Thermal Printer

Part Number		FTP-441MCL001, FTP-441DCL001	FTP-441MCL002, FTP-441DCL002
Figure			
Dot structure [dots/line]		640	640
Horizontal dot pitch [dots/mm (dpi)]		6 (152)	6 (152)
Printing speed [dot lines/s]		250	170
Dimensions W x D x H [mm (in.)]	Mechanism	164 x 60 x 40 (6.457 x 2.362 x 1.575)	164 x 60 x 40 (6.457 x 2.362 x 1.575)
	Interface board	140 x 89 x 19 (5.512 x 3.504 x 0.748)	140 x 89 x 19 (5.512 x 3.504 x 0.748)
Weight [g]	Mechanism	600	600
	Interface board	150	150
Power supply voltage [V]		24/5	24/5
Paper width [mm (in.)]		114 (4.488)	114 (4.488)
Remarks		1 ply paper type Centronics standard interface UL recognized	2 ply paper type Centronics standard interface UL recognized

High-Speed Thermal Printer

Part Number		FTP-441MCL002, FTP-441DCL004	FTP-441MCL001, FTP-441DSL001
Figure			
Dot structure [dots/line]		640	640
Horizontal dot pitch [dots/mm (dpi)]		6 (152)	6 (152)
Printing speed [dot lines/s]		250	154
Dimensions W x D x H [mm (in.)]	Mechanism	164 x 60 x 40 (6.457 x 2.362 x 1.575)	164 x 60 x 40 (6.457 x 2.362 x 1.575)
	Interface board	140 x 89 x 19 (5.512 x 3.504 x 0.748)	140 x 140 x 20 (5.512 x 5.512 x 0.787)
Weight [g]	Mechanism	600	600
	Interface board	150	160
Power supply voltage [V]		24/5	24/5/±12
Paper width [mm (in.)]		114 (4.488)	114 (4.488)
Remarks		Thick paper/label form type Centronics standard interface UL recognized	1 ply paper type RS-232C standard interface UL recognized