

UNIVAC 9700

MANAGEMENT SUMMARY

With the announcement of the 9700 on November 9, 1971, UNIVAC finally unveiled the long-promised larger member of the Series 9000 family. Since the introduction of the Series 9000 in June 1966 with the small-scale UNIVAC 9200 and 9300, the family has steadily but slowly grown larger with the progressive announcement of the 9200 II, 9300 II, and 9400. Each new system has provided increased capabilities while maintaining upward compatibility with its Series 9000 predecessors.

The newly arrived UNIVAC 9700 delivers about three times the internal performance of the 9400, together with new features that make it comparable to the IBM System/370 Model 145. The 9700 uses essentially the standard IBM System/360 instruction set. This, together with appropriate software support, will make it almost completely compatible with System/360 DOS.

The 9700's main memory capacity spans an unusually wide range from 65K to more than one million bytes. In addition to the monolithic integrated circuits and plated-wire memory used in previous versions of the UNIVAC 9000 series, the 9700 uses a separate plated-wire writable control storage for microprograms. Thus, the 9700's architecture is similar in many respects to that of the IBM System/370, except that additional control storage in the 9700 does not use up any main memory capacity, as it does in the IBM 370/145.

The long-awaited 9700 fulfills UNIVAC's promise of a larger member of the Series 9000 family and provides almost complete compatibility with the popular IBM System/360 DOS. A wide range of memory capacity and advanced features such as microprogramming make this general-purpose system a significant alternative to the medium-scale IBM 370/145.

CHARACTERISTICS

MANUFACTURER: UNIVAC Division, Sperry Rand Corporation, P.O. Box 500, Blue Bell, Pa. 19422.

MODEL: UNIVAC 9700

DATA FORMATS

BASIC UNIT: 8-bit byte. Each byte can represent 1 alphanumeric character, 2 decimal digits, or 8 binary bits. Two consecutive bytes form a 16-bit "halfword," four consecutive bytes form a 32-bit "word," and eight consecutive bytes form a 64-bit "doubleword."

FIXED-POINT OPERANDS: Can range from 1 to 16 bytes (1 to 31 digits plus sign) in decimal mode; 1 halfword (16 bits) or 1 word (32 bits) in binary mode. Certain operations use a doubleword (63-bit integer field plus sign) in binary mode.

FLOATING-POINT OPERANDS: Optional floating-point hardware provides for addition, subtraction, multiplication, division, loading, storing, and sign control of short or long format operands. The short format provides 24-bit precision



This view of a fairly small, disc-oriented UNIVAC 9700 configuration shows the CRT-equipped System Console in the foreground and the Central Processor at left rear.

UNIVAC 9700

▷ The Series 9000 instruction repertoire has been expanded from the previous subset of IBM System/360 instructions to include, in the 9700, the complete set of System/360 Model 50 instructions. The UNIVAC 9700 also features an optional high-speed Operating System Storage Facility (OSSF) to contain up to 12 million bytes of non-resident operating system segments. The OSSF is a fixed head-per-track disc storage facility and uses a dedicated channel which does not cause interference with other multiplexer or selector channel operations.

A broad range of peripheral devices is available for the 9700, including top-of-the-line tapes and discs which UNIVAC formerly offered only for the large-scale 1100 Series computers. The Uniservo 20 Magnetic Tape Unit (320,000 bytes per second) and the 8440 Disc Storage Facility (up to 880 million bytes on-line) provide high-performance data storage and retrieval capabilities which far exceed those of the smaller models in the Series 9000. Other specific enhancements, in addition to the OSSF mentioned above, include a Communications Intelligence Channel (CIC), an integrated IBM 1401, 1440, and 1460 emulation feature, and floating-point hardware; the latter two features are supported by microprograms in the writable control storage.

Software support for the UNIVAC 9700 consists of the full program library for the earlier UNIVAC 9400 plus two operating systems: OS/4, which is essentially an expansion of the current UNIVAC 9400 operating system; and the advanced OS/7, which will fully implement the new hardware features of the 9700.

OS/4 will be available with the first delivery of the 9700 in August 1972, and OS/7 will be released in an initial version during the first quarter of 1973, with continuing releases planned for some language processors. At that time, unless intervening announcements by other vendors provide more cost-effective upgrades, the UNIVAC 9700 will provide a strong alternative to the IBM 370/145, and may well be the *only* system to offer a viable intercept to the industry giant's planned migration strategy for existing customers—including almost complete compatibility with the System/360 DOS user software. This compatibility will also extend to IBM Program Products, which can be licensed by individual UNIVAC 9700 users, and to other IBM applications software in the public domain.

In recognition of the necessity to ease "executive anxiety" on the part of UNIVAC 9700 prospects who may contemplate conversion from some other vendor's computer to the new 9700 system, UNIVAC has initiated a free conversion support program. This program will be administered through Customer Support Facilities which will be located near key concentrations of UNIVAC 9700 prospects and customers. Use of these facilities is primarily intended for conversion of eligible user DOS software, which will usually consist of source programs whose language specifications conform to ANS standards. ▷

▶ and is represented by one word, which uses bit 0 for the sign, bits 1 through 7 for the exponent, and bits 8 through 31 for the fraction. Long format is represented with a doubleword which provides 56-bit precision; the long format is similar to the short format except that the fraction is contained in bit positions 8 through 63. A guard digit is carried by the hardware for intermediate "place holding" during addition/subtraction, multiplication, comparison, and halving.

INSTRUCTIONS: 2, 4, or 6 bytes in length, specifying 0, 1, or 2 main storage addresses, respectively.

INTERNAL CODE: EBCDIC or ASCII, depending upon setting of a mode bit in the program status word by certain processor instructions. The processor is sensitive to zone fields and edit control characters.

MAIN STORAGE

STORAGE TYPE: Plated-wire (a thin-film memory technique).

CAPACITY: From 65,536 to 1,048,576 bytes in ten sizes: 65K, 131K, 196K, 262K, 393K, 524K, 655K, 786K, 917K, or 1,048K bytes.

CYCLE TIME: 0.6 microsecond per 4-byte access.

CHECKING: Parity bit with each byte is generated during writing and checked during reading, with additional parity generation and checking provided on the channels and memory busses.

STORAGE PROTECTION: The standard Storage Protection feature uses 16 keys to provide read and/or write protection for 2048-byte blocks of storage. An interrupt is generated whenever a read or write instruction is attempted in an unauthorized storage location.

RESERVED STORAGE: The first 640 bytes of main storage are reserved to hold specific operating information.

CENTRAL PROCESSORS

REGISTERS: The programmer has access to sixteen 32-bit general registers that are used for indexing, base addressing, and as accumulators. (A second full set of 16 registers is used by the operating system.)

Sixteen additional standard program relocation registers in low-order main storage serve as base registers for the program modules in main memory; two of these registers are reserved for the operating system. These program relocation registers facilitate the OS/7 rollout/rollin capability. Four doubleword floating-point registers are optional.

INDIRECT ADDRESSING: The 9700 uses 3 non-privileged instructions to provide an indirect addressing function for up to 8 levels. These instructions also assist in relocation and permit branching to subroutines while bypassing the operating system.

CONTROL STORAGE: In addition to main storage, a fast writable control storage of from 2K to 6K 72-bit words (16K to 48K bytes) is available for the microprograms used to support integrated emulation, floating-point hardware, microdiagnostics, and the native-mode instruction set. UNIVAC has priced each of these to include the control storage required for its own microprogram support. The cycle speed of this separate plated-wire memory is expected to be 80 nanoseconds per 72-bit word access. Data ▶

UNIVAC 9700

▷ Reacting to the demise of RCA as a mainframe computer manufacturer in mid-September 1971, UNIVAC coordinated the product development plans for its 9700 computer system with its takeover of the RCA customer base (which was scheduled to become effective on December 31, 1971). Thus, in little more than three months, UNIVAC took decisive steps in a calculated bid to acquire the installed RCA customer base of more than 1000 systems at over 500 accounts, plus responsibility for RCA systems on order. With these steps, UNIVAC has acted to exploit its opportunity to penetrate the RCA customer base to the fullest extent possible with the UNIVAC 9700 and has moved to regain the undisputed Number Two spot among computer vendors in terms of value of product shipped. This title, long held by UNIVAC, was yielded to Honeywell Information Systems in October 1970 following Honeywell's acquisition of the GE computer interests.

Other UNIVAC marketing objectives for the 9700 include: (1) protection of its own base of 9400 systems, many of which have attained maturity since the 9400 was introduced in January 1968; (2) provision of an upgrade alternative to the IBM 370/145 for the installed IBM base of more than 10,000 360/30's, more than 5,000 360/40's, and a modest number of 360/50's operating under DOS; (3) development of a compatibility bridge to facilitate upward growth for a total of about 6,000 IBM 1401, 1440, and 1460 installations; and (4) compatibility for 1401, 1440, and 1460 programs currently being emulated on IBM System/360 computers.

While the likelihood is strong that the UNIVAC 9700 will effectively protect the installed 9400 customer base, UNIVAC's hoped-for interception of the migration of System/360 users to the System/370, as well as its success in penetrating the IBM and RCA customer bases, depends heavily upon magnanimity from the industry giant and the price-performance of the UNIVAC 9700 itself.

While the UNIVAC 9700 purchase and long-term lease prices compare very favorably with those of the 370/145 for comparable systems, many RCA users who feel that they were "left holding the bag," as well as numerous System/360 users who may have been considering "leaving the IBM fold," are now strongly inclined toward selecting or remaining with IBM as their mainframe vendor.

Offering a first alternative to the 370/145 as an upgrade for IBM System/360 Model 30, 40, and 50 DOS users could be a highly profitable move for UNIVAC. IBM's installed base of about 15,000 Model 30's and 40's, as well as Model 50 DOS systems, will be an average of five or six years old by the time UNIVAC delivers source-level compatibility for most System/360 DOS user software through release of OS/7 during 1973.

In order for its \$70-million-plus gambit to succeed in attracting former RCA customers to the 9700, UNIVAC ▷

▶ will be loaded into the writable control storage via a cassette prepared by UNIVAC support personnel.

INSTRUCTION REPERTOIRE: All 132 nonprivileged instructions of the IBM System/360 instruction set are provided, including an add immediate instruction, 3 indirect addressing function instructions, an emulation aid instruction, and optional floating-point instructions. The standard instructions handle fixed-point binary arithmetic and decimal arithmetic using variable-length operands in packed formats, and include instructions for packing and unpacking, radix conversion, editing, loading, storing, comparing, shifting, branching, and logical operations, as well as instructions for handling ASCII or EBCDIC characters.

INSTRUCTION TIMES: All times are estimated for register-to-indexed-storage (RX) instructions and are given in microseconds.

Binary add/subtract (32 bits):	1.50
Floating-point add/subtract (short):	6.17
Floating-point multiply (short):	11.90
Floating-point divide (short):	28.20
Floating-point add/subtract (long):	6.87/6.97
Floating-point multiply (long):	35.30
Floating-point divide (long):	71.25
Decimal add (2-address, on signed 5-digit fields):	12.60

EMULATION: Integrated IBM 1401, 1440, and 1460 emulation is available with the optional 1400 Emulation Control feature, permitting direct execution of programs being emulated on an IBM System/360. More than one emulation can proceed concurrently with other UNIVAC 9700 native-mode processing. See the "Utility Routines" entry in the Software section of this report for further information.

INPUT/OUTPUT CONTROL

I/O CHANNELS: One multiplexer channel, which can physically connect up to 7 low-speed subsystem controllers and a Data Communications Subsystem (DCS) for an aggregate of 15 subchannel addresses. The Subchannel Expansion feature provides an additional 16 subchannels. The Expanded Interface feature can be added to provide up to 8 additional physical controller connections for a total of 16 controllers if the Subchannel Expansion feature has been added; otherwise, up to 7 additional controllers can be attached, not to exceed 15 physical subsystems. The maximum aggregate multiplexer channel transfer rate is 175,000 bytes per second.

One selector channel is standard on the UNIVAC 9700, and three additional selectors can be added. Eight high-speed device controllers can be attached to each selector channel for a maximum throughput of 833,000 bytes per second per channel on a data path 4 bytes wide. Each control unit can attach up to 16 I/O devices. Only one device can transfer data to or from main memory along a given selector channel at a time. Thus, simultaneous access of two or more high-speed devices requires that each be connected to a different selector channel. The second selector channel is housed in the processor cabinet, and selector channels 3 and 4 require the Channel Expansion Cabinet.

The UNIVAC 9700 also provides for direct memory attachment of the optional OSSF (Operating System Storage Facility) through the OSSF Control Channel. ▶

UNIVAC 9700

▷ will have to provide support for and prevent erosion of the installed RCA base over an average period of about two years. During this time before volume shipments of the 9700 begin, many current RCA users will be under strong internal pressure to stop experimenting with other vendors and switch (or return) to IBM. Meanwhile UNIVAC will be called upon not only to overcome this "executive anxiety," but also to provide interim solutions to the RCA users' data processing requirements to keep them from switching vendors out of technical necessity. Neither task will be without its share of headaches for UNIVAC, and the amount of pressure IBM will apply to loyal RCA growth customers as well as "renegade" former IBM customers can be expected to mount steadily if voluntary conversions to IBM do not materialize readily. At the time of this writing, most IBM sales attention has been directed toward the major RCA accounts, with a "let them invite you in first" directive issued generally to IBM salesmen concerning the smaller RCA installations. This directive cannot be expected to survive long after UNIVAC's takeover of the RCA accounts.

With the full IBM instruction set, the separate control memory, the OSSF, and other improvements over earlier Series 9000 systems, the UNIVAC 9700 offers attractive advantages in processing capability per dollar when compared to its IBM 370/145 competition. The 9700 offers instruction execution speeds which are stated to be from 7 to 35 percent faster than those of the 370/145. While UNIVAC's one-year lease rates are, at most, only about 10 percent less than those for the 370/145, UNIVAC's purchase prices and 5-year rental rates for the 9700 are from 15 to 25 percent lower than IBM's purchase prices and 2-year rental rates for comparably equipped 370/145 systems. A further price advantage results to 9700 users from UNIVAC's fully bundled software and support policy, which now includes conversion support at the new Customer Support Facilities.

Upward compatibility of source programs written for smaller Series 9000 machines, as well as for System/360 and System/370 computers, will be excellent. Many IBM assembly-language programs can be run on the 9700 after compilation on the UNIVAC system without recoding. The only types of programs which almost invariably will require recoding are those using communications software. Input data files may require conversion from competitive systems, and this work can be done by UNIVAC at a Customer Support Facility. IBM 1401, 1440, and 1460 programs being emulated on a System/360 can be run on the UNIVAC 9700 by using the integrated 1400 Series Emulator, which is supported by software under OS/7.

The 9700 is a well-balanced system that is nicely suited for either commercial or scientific applications and supported by two operating systems, a full range of peripheral capability, and software which has evolved from the existing Series 9000 systems. Thus, the 9700 seems well

▶ A Direct Control feature (not supported under OS/4) is used to provide a special interface between two UNIVAC 9700 processors and includes two instructions for transfer of control information between the processors.

CONSOLE: 9700 System Console consists of a keyboard with operator controls and a UNISCOPE 100 CRT display unit. The standard mode of operation provides for display of messages on the CRT screen; hard copy is provided by the Console Printer as an optional feature under OS/7, but is required for operation under OS/4. Under OS/7, those error messages which are printed on the console printer with OS/4 are written on magnetic tape for subsequent high-speed printing at the system manager's convenience. The hardcopy Console Printer operates at up to 30 cps and connects to the processor via the multiplexer channel; it uses one physical controller connection on the multiplexer. The 9700 System Console may be switched by the Multiple Channel Switch to operate on a selector channel for diagnostic purposes if required.

The 9000 Series Channel Adapter, which provides either a multiplexer or selector interface to a UNIVAC 9200/9300/9400/9700 subsystem, is housed in the 9700 System Console.

A Multiple Channel Switch (MCS) is available to provide a capability for switching a subsystem or string of subsystems from a multiplexer or selector channel on one processor to the same type of channel on another processor or the same processor. Included with the basic MCS is cabinetry, a power supply, an operator's panel, and space for 5 additional MCS Expansion switches.

CONFIGURATION RULES: High-speed peripheral devices, such as Uniservo 12, 16, or 20 Magnetic Tape Units or 8411, 8414, or 8440 Disc Drives, must be connected to a selector channel. Up to eight control units can be connected to each selector channel.

Low-speed devices, including Univervo VI C Magnetic Tape Units, Data Communications Subsystems, card readers, line printers, and the 9700 System Console, are normally connected to the multiplexer channel, which can accommodate up to 16 control units and 31 subchannel addresses.

SIMULTANEOUS I/O OPERATIONS: Concurrently with computing, the 9700 Processor can control multiple I/O operations with a combined data rate of up to 175,000 bytes/sec on the multiplexer channel, plus one I/O operation with a data rate of up to 833,000 bytes/sec on each selector channel, plus dedicated channels for OSSF data transfer at up to 624,000 bytes/sec and CIC data transfer at a rate of 60,000 bytes/sec.

MASS STORAGE

UNIVAC 9700 OPERATING SYSTEM STORAGE FACILITY (OSSF): Provides a dedicated auxiliary storage device consisting of a head-per-track single-spindle disk subsystem interfaced directly to main memory via the independently functioning OSSF Control Channel. Each OSSF has an 8.34-millisecond average access time, stores 3 million bytes, and can transfer data at a maximum of 321,000 bytes per second. Certain randomly organized user files may be assigned to the OSSF, permitting an improvement in file access times for those sequential files which otherwise would have shared an 8414 or 8440 disk. According to UNIVAC, the addition of the OSSF permits accesses from 2 to 3 times as fast for an 8414 and up to twice as fast for an 8440, with an increase in processor throughput estimated

UNIVAC 9700

► qualified to meet its marketing objectives. Its reception in the marketplace is likely to be heavily influenced by two key factors whose ultimate impact is difficult to assess at this writing: UNIVAC's success in delivering the promised full compatibility with System/360 DOS, and the increasing reluctance among many computer buyers to deal with mainframe suppliers other than IBM. □

► by UNIVAC to be about 20 percent. The OSSF comes with a special channel that can transfer data at a rate of 624,000 bytes per second. This channel can be shared by up to three additional OSSF expansion files, for a maximum storage capacity of 12 million bytes. The OSSF is supported only under OS/7.

8411 DISC DRIVE: Provides interchangeable disc-pack storage of moderate capacity. Each disc pack contains six 14-inch discs, weighs 10 pounds, holds up to 7.25 million bytes of data, and is compatible with the IBM 1316 Disk Pack used in IBM 2311 Disk Storage Drives. One read/write head serves each of the 10 recording surfaces. Up to 36,250 bytes (10 tracks) can be read or written at each position of the comb-type access mechanism. Average head movement time is 75 milliseconds, average rotational delay is 12.5 milliseconds, and data transfer rate is 156,000 bytes per second. Record lengths are variable.

Up to eight 8411 Disc Drives (58 million bytes) can be connected to a Disc File Control, and up to eight controls can in turn be connected to each UNIVAC 9700 selector channel. The following options are available: File Scan, which permits searching of data areas as well as record keys; Record Overflow, which permits records longer than one track (3625 bytes); and Dual Channel, which allows two different computers or two different selector channels on the same computer to non-simultaneously access an 8411 subsystem.

8414 DISC DRIVE: Provides large-capacity random-access storage in interchangeable 11-disc packs which are compatible with the IBM 2316 Disk Packs used in the IBM 2314 Direct Access Storage Facility. Each pack stores up to 29.17 million bytes of data. Up to 145,880 bytes (20 tracks) can be read or written at each position of the comb-type access mechanism. Average head movement time is 60 milliseconds, average rotational delay is 12.5 milliseconds, and data transfer rate is 312,000 bytes/sec. Record lengths are variable.

From two to eight 8414 Disc Drives can be connected to a Disc Control, providing from 48.4 to 233.4 million bytes of on-line storage. Up to eight Disc Controls, in turn, can be connected to each UNIVAC 9700 selector channel. The File Scan and Record Overflow features are standard, and the Dual Channel capability is optional. With addition of the 8411 Capability option, any combination of up to eight 8411 and 8414 drives may be connected to the Disc Control.

8440 DISC SUBSYSTEM: Provides rapid access to extremely large quantities of data stored in interchangeable 11-disc packs. Data is stored in a byte mode, with each pack holding up to 110,222,800 8-bit bytes. Each of the 19 data recording surfaces has 400 addressable tracks, and each track holds up to 14,503 bytes. Up to 275,557 bytes (19 tracks) can be read or written at each position of the comb-type access mechanism. Average head movement time is 35 milliseconds, average rotational delay is 12.5 milliseconds, and data transfer rate is 624,000 bytes per second.

The File Scan and Record Overflow features are standard for the 8440 subsystem.

An 8440 subsystem consists of a control unit and from one to eight disc drives for a maximum capacity of 880 million bytes on-line. Each drive is housed in a separate cabinet. The optional Dual Access feature on two controllers permits concurrent read/read, read/write, or write/write operations on two of the drives in a subsystem. Initial deliveries of the 8440 are scheduled for the second quarter of 1972. The disc packs used with the 8440 are not compatible with those used with the IBM 3330, IBM 2314, or UNIVAC 8414 drives; UNIVAC believes its use of nickel-cobalt plating on the recording surfaces of the 8440 pack will lead to higher reliability than the oxide coatings used on most other packs.

INPUT/OUTPUT UNITS

UNISERVO VI C MAGNETIC TAPE UNIT: A low-cost tape drive that reads and records data on standard 1/2-inch tape in IBM-compatible NRZI formats. Available in 9-track version only for the UNIVAC 9700. Tape speed is 42.7 inches per second, forward or backward, and data transfer rate is 34,160 bytes per second at 800 bpi. A Uniservo VI C Subsystem consists of a control unit and from 2 to 8 tape drives. The subsystem must be connected to a shared multiplexer subchannel of the 9700 Processor.

UNISERVO 12 MAGNETIC TAPE UNIT: A medium-speed tape drive that reads and records data on standard 1/2-inch tape in IBM-compatible phase-encoded or NRZI format. Available in both 9-track and 7-track versions. Tape speed is 42.7 inches per second, forward or backward. The standard 9-track version has a recording density of 1600 bpi (in phase-encoded mode) and a data rate of 68,320 bytes per second; the optional Dual Density feature permits operation at 800 bpi (in NRZI mode) at a data rate of 34,160 bytes per second—the same speed as the Uniservo VI C. The 7-track version can operate at 200, 556, or 800 bpi, with corresponding data rates of 8,540, 23,740, or 34,160 characters per second. The Data Conversion feature, for 7-track drives, converts each group of four 6-bit characters from tape into three 8-bit bytes in main storage, and vice versa.

From 1 to 16 Uniservo 12 Tape Units can be connected to a Uniservo 12 tape control, and up to 8 controls can in turn be connected to each UNIVAC 9700 selector channel. Optional features enable the tape control to be connected to two selector channels, permitting simultaneous read/read, read/write, or write/write tape operations, with bi-modal (7- or 9-track) compatibility.

With addition of the Uniservo 16 Capability option, any combination of up to sixteen Uniservo 12 and Uniservo 16 drives may be connected to the Uniservo 12 Control. A Uniservo 12/16 Control is also available which includes the Uniservo 16 Capability as a standard feature.

UNISERVO 16 MAGNETIC TAPE UNIT: A high-speed tape drive that reads and records data on standard 1/2-inch tape in IBM-compatible phase-encoded or NRZI formats. Available in both 9-track and 7-track versions. Tape speed is 120 inches per second, forward or backward. The standard 9-track version has a recording density of 1600 bpi (in phase-encoded mode) and a data rate of 192,000 bytes per second; the optional Dual Density feature permits operation at 800 bpi (in NRZI mode) at a data rate of 96,000 bytes per second. The 7-track version operates at 200, 556, or 800 bpi, with corresponding data rates of 24,000, 66,720, or 96,000 characters per second. ►

UNIVAC 9700

► From 1 to 16 Uniservo 12 and Uniservo 16 Tape Units can be connected to a Uniservo 12/16 Control, or any combination of 1 to 16 Uniservo 12, 16, or 20 Tape Units can be connected to a Uniservo 20 Control, and up to 8 tape controls can in turn be connected to each UNIVAC 9700 selector channel. Optional features enable the tape control to be connected to two selector channels, permitting simultaneous read/read, read/write, or write/write tape operations.

UNISERVO 20 MAGNETIC TAPE UNIT: A high-speed tape drive that reads and records data on standard 1/2-inch tape in IBM-compatible formats. Available in a 9-track version only. Tape speed is 200 inches per second, forward or backward. The Uniservo 20 has a recording density of 1600 bpi (in phase-encoded mode) and a data rate of 320,000 bytes per second. Standard features include a power window, automatic tape threading, and a wrap-around cartridge.

From 1 to 16 nine-track, 800 or 1600 bpi Uniservo 12, 16, and/or 20 Tape Units can be connected in any combination to the Uniservo 20 Control Unit, and up to 8 tape controls can in turn be connected to each UNIVAC 9700 selector channel. With the 7-Track Capability and 9-Track Addition feature, Uniservo 12 and 16 Tape Units in the Uniservo 20 subsystem may be 7- or 9-track. Two or more control units may be used in the Uniservo 20 Subsystem to provide simultaneous dual access for read/write, read/read, and write/write operations on any appropriately equipped Uniservo 16 or 20 Tape Units connected to the control units. Each control unit in a simultaneous dual access system has its own power supply and independent access path to provide increased reliability. Individual tapes cannot be switched off-line without removing all the tapes connected to that controller from service.

600-CPM CARD READER, 0711-05: Reads 80-column cards serially by column at 600 cpm. Can be equipped to read 51- or 66-column short cards. Reads in either EBCDIC or card-image mode. A Validity Check option can detect the presence of more than one punch in rows 1 through 7 of any card column. Has a 1200-card feed hopper and one 1500-card stacker. Connected via the multiplexer channel.

1000-CPM CARD READER, 0716-99: Reads 80-column cards serially by column at 1000 cpm. Can be equipped to read 51- or 66-column short cards. A Validity Check option can detect the presence of more than one punch in rows 1 through 7 of any card column. Has a 2400-card input hopper and two 2000-card output stackers. Reads in either EBCDIC or card-image mode under program control; an ASCII translator is optional. Connected via the multiplexer channel.

250-CPM CARD PUNCH, 0604-99: Punches 80-column cards in row-by-row fashion at 250 cpm, in either EBCDIC or card-image mode. Has a 1000-card feed hopper and two 1000-card output stackers, with program control of stacker selection. Can be equipped with a pre-punch read station, giving the unit read/punch capabilities. Connected via the multiplexer channel.

PAPER TAPE SUBSYSTEM: Consists of a 300-char/sec F1033-02 reader, 110-char/sec F1032-02 punch, and 0920-02 control unit in a single cabinet. Reads and punches 5-, 6-, 7-, or 8-level tape. Spoolers are optional for both the reader and punch take-up. Connected via the multiplexer channel.

900/1100-LPM PRINTER, 0768-00: Prints at 900 lpm when the full 63-character set is used and at 1100 lpm when using any 49 contiguous characters. Uses a conventional rotating-drum print mechanism. Has 132 print posi-

tions. Skipping speed is 33 inches per second at the normal vertical spacing of 6 lines per inch. Alternate 8-lines-per inch spacing is also standard. Connected via the multiplexer channel.

1200/1600-LPM PRINTER, 0768-99: Prints at 1200 lpm when the full 63-character set is used and at 1600 lpm when using any 43 contiguous characters. Uses a conventional rotating-drum print mechanism. Has 132 print positions. Skipping speed is 33 inches per second at the normal vertical spacing of 6 lines per inch. Alternate 8-lines-per inch spacing is also standard. Connected via the multiplexer channel.

840/1000/2000-LPM PRINTER 0768-02: Features upper-and-lower-case alphabetic printing plus high-speed numeric printing. Each of the 132 print positions has 94 discrete characters, with the 10 numerics and 4 special characters duplicated on opposite sides of the drum. Peak printing speed is 2000 lpm for numerics (at single, double, or triple spacing), 1000 lpm for up to 87 contiguous characters, and 840 lpm when all 94 characters are used. A choice of three character sets is offered, all in the UNIVAC H-14 font which is readable by the 2703 Optical Document Reader. A Print Code Expansion feature allows logical expansion of the character set to 108 different characters. Skipping speed is 33 inches per second. Connected via the multiplexer channel. Deliveries are scheduled to begin in the second quarter of 1972.

2703 OPTICAL DOCUMENT READER: Reads printed numeric data from individual documents ranging from 2.75 to 4.25 inches in height and 2.00 to 8.75 inches in length. Basic speed of 300 six-inch documents per minute can be increased to 600 dpm by an optional feature. Other options permit reading of vertical pencil marks and of standard 80-column punched cards. The Modulus-10 Check Digit option compares a computed modulus-10 check digit with a check digit printed on the document. Character set consists of the digits 0-9 and four special symbols, in either UNIVAC H-14, OCR-A, or OCR-B (ECMA) font. Has a 2000-document feed hopper and three 1000-document stackers. Connected via the multiplexer channel.

9700 CHANNEL ADAPTERS: Permit any of the following small-to-medium-scale UNIVAC data processing systems to be connected to the 9700 for communication via their respective multiplexer or selector channels: 9200, 9200 II, 9300, 9300 II, 9400, or 9700. Each attachable processor may function as an I/O subsystem providing peripheral capabilities. For details of the smaller Series 9000 computer systems, please refer to DATAPRO 70 Reports 70C-877-01 and 70C-877-02.

COMMUNICATION CONTROLS

COMMUNICATIONS INTELLIGENCE CHANNEL (CIC): An independently operating channel with programmable message control logic is available as an option for specialized message control of up to 128 half-duplex or 64 full-duplex lines. The CIC is functionally similar to a multiplexer channel that is dedicated to communications devices, and transfers data at a maximum throughput rate of 60,000 bytes per second to and from the terminals which are connected to it.

DATA COMMUNICATIONS SUBSYSTEMS: Remote communications devices can also be connected to a UNIVAC 9700 system by means of from one to four Data Communications Subsystems. The DCS-1, DCS-1C, DCS-4, and ►

UNIVAC 9700

► DCS-16 subsystems can accommodate 1, 1, 4, and 14 half-duplex or full-duplex lines, respectively. Each DCS is connected directly to a multiplexer subchannel. Any combination of up to 4 DCS's may be connected to a UNIVAC 9700, subject to a limit of 14 lines maximum.

Each DCS consists of a single Line Terminal Controller, plus a Line Terminal and a Communications Interface for each connected line. Numerous models of line terminals and interfaces permit asynchronous and/or synchronous transmission over a wide range of communications services at speeds of 75 to 250,000 bits per second. The DCS-1C is a Binary Synchronous Data Communications Subsystem that enables a 9000 Series computer to communicate with an IBM System/360 computer, using either EBCDIC or ASCII code and either Transparent or Nontransparent mode. The free standing 8577-02 DCS Cabinet used with the DCS-1 or DCS-1C houses up to 4 of these units in any combination. The DCS-4 or DCS-16 includes its own free-standing cabinet and power supply.

COMMUNICATIONS TERMINALS: The Uniscope 100 Display Terminal (Report 70D-877-05), the DCT 500 (70D-877-02), the DCT 1000 (70D-877-03), and the DCT 2000 (70D-877-01) are available for use with the UNIVAC 9700. Please refer to the indicated DATAPRO 70 Peripherals reports for complete coverage of these devices.

SOFTWARE

OPERATING SYSTEMS: Two operating systems are available for the UNIVAC 9700: OS/4, an enhanced version of the UNIVAC 9400 Disc Operating System; and OS/7, a new operating system developed to fully utilize the 9700's hardware. Essentially similar language processors are available for both operating systems which range in size from about 40K to 48K bytes.

Programs developed for either OS/4 or the UNIVAC 9400 are upward-compatible at the source level with OS/7 language processors. Those programs, however, must be recompiled in order to run under OS/7.

OS/4: Provides essentially the same facilities as the UNIVAC 9400 DOS and is disc-oriented; no tape-oriented version is available. Enhancements which have been made to 9400 DOS consist of modifications to support the 9700 console and the extra channels and larger memory of the 9700. OS/4 requires at least two disc drives, a processor with 65K bytes of main memory, a card reader, and a printer (or a smaller UNIVAC computer connected as an I/O subsystem). Minimum resident memory requirement for OS/4 is about 24K bytes.

The system control facilities of OS/4 are divided into four main categories: Supervisor, Job Control, Data Management, and Message Control.

The Supervisor resides in main storage and schedules and coordinates all activities within the system. Its functions include interrupt handling, I/O scheduling and initiation, job time allocation, operator communication, job accounting, and control of multiprogrammed operations. Up to five independent programs can be executed concurrently if sufficient memory and peripherals are available. The Supervisor provides five different priority levels, three of which are available for users' programs.

The OS/4 Job Control routine controls transitions between job steps, suspension or cancellation of jobs, restarting of

jobs, and termination of jobs. It receives its instructions from control cards which constitute a "job stream." Job streams can be stored in disc files for subsequent selection and execution.

Data Management provides comprehensive input/output control facilities, including record blocking and unblocking, I/O buffering, data validation, and label processing. These facilities are provided by subprograms which are generated as part of the operating system and referenced by macro-instructions in users' programs. Nonsequential files in disc storage can be accessed by either the Direct (random) Access Method, in which the user must specify the relative or absolute address of the desired disc record, or the Indexed Sequential Access Method, in which the user need only specify the key of the desired record. In a multiprogramming environment, the Data Management routines can be shared by all programs, thereby reducing main storage requirements.

The OS/4 Message Control Program provides macro-instructions that enable the user to generate custom-tailored message control and message processing routines to handle communications input/output. Messages of fixed or variable length can be queued in main and/or disc storage, and the generated routines can perform functions such as code translation, message sequencing, time stamping, and error checking. Use of the full Message Control Program services requires a minimum of 65K bytes of main storage.

UNIVAC 9700 OPERATING SYSTEM (OS/7): Provides additional facilities beyond OS/4, which include multiprogramming with up to 14 concurrent variable-length jobs, swapping to an optional Operating System Storage Facility (OSSF), improved data management system and system cataloging procedures, job accounting, automatic job scheduling, on-line diagnostics, remote job entry, and integrated IBM 1401, 1440, and 1460 emulation. An Information Management System (IMS/7) has also been released with the announcement of the 9700. Release of OS/7 is scheduled for the first quarter of 1973, with later releases providing full support for the OSSF and CIC as well as certain language processors.

OS/7 is a disc-oriented system that requires a minimum configuration consisting of a processor with 131K bytes of main memory, either two disc drives and a magnetic tape unit or three disc drives, a card reader and a printer (or a smaller UNIVAC computer connected as an I/O subsystem). At least 48K bytes are required for the minimum operating system residence. Expanded versions of OS/7, including the full message control and data management elements, may require up to 124K bytes of memory plus additional memory requirements for language processors, emulation, and IMS/7. The System Control facilities of OS/7 are divided into four main categories: Supervisor, Job Control, Data Management, and Communications.

The Supervisor resides in main storage and consists of the system modules which perform storage management, task management, I/O control, timer service, program management, system recovery, spooling control, record and file protection, control of diagnostic and debug aids, system console management, and the subroutine linkage table. At the time the supervisor is generated (SYSGEN), the number of priorities and initial time-slice lengths for each priority level are specified. These priorities are recorded in a system switch list, which is managed by the Task Manager routine. Priorities may be changed for a given job at run time within limits which are also established at SYSGEN time. ►

UNIVAC 9700

► Software operating efficiency can be improved through attachment of the dedicated Operating System Storage Facility (OSSF). According to UNIVAC, the OSSF will typically yield about a 20 percent increase in throughput. This head-per-track disc connects through its own Control Channel directly to the processor and is managed by the Supervisor. OSSF files are accessed using the System Integrated Access Method (SIAM) and include OS/7 transient routines and overlays, parts of the System Catalog, OS/7 checkpoint information, and scratch areas for sorts and language processors. Program relocation and input and output spooling are also controlled by the Supervisor. Output writers to remote devices allow batch programs to service remote users, thus providing a Remote Job Entry capability. Minimum main storage requirement for the Supervisor is 46K bytes.

The OS/7 Job Control routine controls transitions between job steps, suspension or cancellation of jobs, restarting of jobs, and termination of jobs. It receives its instructions from control cards which constitute a "job stream." Job streams are stored in disc files for subsequent selection and execution. The Job Control routine also performs job accounting, catalog management, and device allocation.

Data Management provides comprehensive interface facilities between user programs and the hardware-oriented I/O control performed by the Supervisor. File organization methods supported consist of Sequential, Direct (random), Indexed Sequential, and System Integrated access methods. Library and work files on the OSSF as well as on other disc or tape devices are supported by the System Integrated Access Method (SIAM), while other user files are written under control of SAM, DAM, or ISAM. Re-entrant logical I/O control modules provide for record blocking and unblocking, I/O buffering, data validation, and label processing. Another important function of Data Management allows the user to take advantage of capabilities in the Supervisor for checkpoint/restart and audit trails for reconstruction and recovery. Main memory requirements for Data Management vary from 14K to 25K bytes.

Communications routines are provided for network definition and control, message handling, logical record interfacing, and handling of communications lines over the Data Communications Subsystem (DCS) or the Communication Intelligence Channel (CIC). The Message Control program interfaces to the Supervisor routines which physically control communications I/O. Message Control is the major communications routine; it provides initiation and control of message flow, message queueing, line control, buffering, reformatting and code conversion, polling, error detection and correction, and interfacing with IMS/7. Optional functions provide for keeping message statistics for traffic analysis, audit trails, and support for automatic store-and-forward of messages and message switching. Memory requirements for the basic communications routines are 21K to 31K bytes, and 31K to 49K bytes are required for the advanced communications routines.

INFORMATION MANAGEMENT SYSTEM (IMS/7): Provides OS/7 users with an on-line information storage and retrieval capability utilizing the Message Control program and the Data Management handlers for standard file access methods. After initiating a dialog with IMS/7, passwords are used to control access to restricted information. A free-form query/update language, supported by either CRT or hardcopy terminal devices, permits users to retrieve and display information from files, generate and display lists of qualified data, and add, delete, or change files. IMS/7 also facilitates applications programming by providing communications interfacing, application program scheduling, data

management, system security, and recovery of files and messages. Main memory requirement for IMS/7 is about 40K bytes, which includes the user-terminal language processor called UNIQUE.

COBOL: UNIVAC offers two COBOL compilers for use under OS/4. Basic COBOL requires a system with 65K bytes of main storage and includes the minimum American National Standard COBOL language facilities (i.e., Level 1 of the Nucleus, Sequential Access, Segmentation, and Table Handling modules). Extended COBOL requires a system with 65K bytes of main storage and two disc drives. It includes the following facilities of ANS COBOL: Level 2 of the Nucleus, Sequential Access, and Table Handling modules, and Level 1 of the Random Access, Sort, and Segmentation modules.

The OS/7 COBOL compiler conforms to DOD Level 4 requirements. It includes the ANS Level 2 Nucleus, Sequential Access, Sort, Segmentation and Library modules, and a Level 3 implementation of the Table Handling module. The Report Writer Feature has not been included. Memory requirement for OS/7 COBOL is 48K bytes.

FORTRAN: An OS/4 FORTRAN compiler is available for operation on the minimum 65K UNIVAC 9700 system. It includes all the language facilities of full American National Standard FORTRAN. In addition, there are more than 20 useful language extensions, such as direct-access I/O statements and the ability to handle arrays of up to 7 dimensions.

The OS/7 FORTRAN Compiler offers essentially the same capabilities as the OS/4 compiler, plus source-code compatibility with IBM System/360 Level F FORTRAN except for the DUMP and PDUMP Statements. OS/7 FORTRAN requires about 40K bytes of main memory.

ASSEMBLER: The OS/4 Assembler permits programs to be coded in a symbolic assembly language that is very similar to, though not totally compatible with, the Assembler languages for the UNIVAC 9200/9200 systems and the IBM System/360. It is directly compatible with the UNIVAC 9400 BAL.

The OS/7 Assembler includes all of the nonprivileged instructions of the IBM System/360 Model 50. Programs written for the UNIVAC 9400 or IBM System/360 Assembler can be assembled using the OS/7 Assembler without change. Memory requirement for the OS/7 Assembler is 40K bytes. The Assembler produces relocatable object modules which can be written on either disc or tape. These object modules can be linked to other modules prior to being loaded and executed. A macro-instruction facility simplifies the inclusion of precoded subprograms

REPORT PROGRAM GENERATOR: The OS/4 RPG is designed to accept UNIVAC 9200/9300/9400 RPG source programs for generation and execution on a 9700. It is available for the minimum UNIVAC 9700 with 65K bytes of main storage. The generated RPG object programs can be recorded on tape, disc, or punched cards to eliminate the need for re-generation of the program before subsequent report runs. The object programs are relocatable modules that can be linked to other programs and stored in disc or tape libraries.

OS/7 RPG offers the same capabilities as the OS/4 version, plus source-code compatibility with IBM System/360 DOS RPG. Memory requirement for OS/7 RPG is 20K bytes. ►

UNIVAC 9700

► **UTILITY ROUTINES:** An OS/4 or OS/7 Sort/Merge program capable of using disc and/or tape drives is available. It can sort fixed or variable-length records into either ascending or descending sequence, and includes provisions for the user's own coding. Disc-only sorts require enough disc capacity to hold all the records to be sorted plus sort control information. Tape-only sorts require 3 to 14 tape units, with no more than 6 tapes used for string collating. Tape/disc sorts use the disc to increase the length of the strings before collation is done on tape. The program's operation can be controlled by parameters entered either when the sort is generated or at run time. Up to 255 noncontiguous key fields can be specified, using shared input devices, if desired, and reserved output devices. The COBOL SORT verb generates a linkage to the Sort/Merge utility program.

A Linkage Editor combines object modules produced by the COBOL, FORTRAN, RPG, or Assembly language translators into "load modules" which are suitable for loading and execution under operating system control.

Library Service routines facilitate the creation and maintenance of various types of libraries on tape and disc for OS/4 or OS/7.

Other available utility programs for either the OS/4 or OS/7 operating system include data transcription routines, comprehensive data utilities to copy data from any input device to any output device, file maintenance routines, a dynamic (snapshot) dump, a terminal (postmortem) dump, and tape and disc listing programs.

For use under OS/4, UNIVAC offers a simulator for the UNIVAC 1050 and translators for IBM 1400 Series Autocoder and SPS and for IBM System/360 BAL.

Under OS/7, the IBM System/360 Assembler language is fully compatible with the UNIVAC 9700 Assembler. IBM 1401, 1440, and 1460 compatibility is handled through microprogrammed integrated emulation for certain time-consuming operations, supported by software subroutines for other emulated operations. More than one object program for the 1401, 1440, and 1460 can be run concurrently with other 9700 operations without reprogramming, using the 1400 Series disc, tape, and unit record files. UNIVAC claims 9700 emulation performance of 5.0 times native 1401 performance and 2.5 times native 1460 performance; these estimates are roughly similar to those claimed for the IBM System/360 Model 40 and the System/370 Model 145. UNIVAC 9700 software support required in conjunction with the special hardware compatibility features and microcode occupies from 45K to 60K bytes of main memory.

APPLICATION PROGRAMS: Programs announced to date include an advanced PERT Management Control System (MCS), LP 9700 (linear programming), UNIS (bill of materials, inventory control, planning and scheduling), PROFITS (on-line bank teller transaction processing), LINCO III (typesetting and line justification), and WIMS (Wholesale Inventory Management System). The 9700's announced compatibility with IBM System/360 DOS user programs will permit the use of most of the existing System/360 application programs, as described in the Management Summary.

PRICING

EQUIPMENT: All necessary control units and adapters are included in the indicated prices for the following typical configurations, and the quoted one-year rental prices include equipment maintenance.

On August 5, 1971, UNIVAC announced a 5% increase in the purchase and rental prices and a 7% increase in the monthly maintenance charges for most of the peripheral equipment that will be used with the 9700. But as a result of the ensuing wage/price freeze, these increases have been

postponed indefinitely, if not permanently. Therefore, all of the following prices are the ones which were in effect prior to August 5 and are still in effect at this writing.

SMALL TAPE/DISC SYSTEM (USING OS/4): Consists of 131K Processor (with standard selector, multiplexer, and storage protection feature) Console, 600-cpm Card Reader, 250-cpm Card Punch, 900/1100-lpm Printer, two Uniservo VI C (34KB) Tape Units with control, and two 8414 Disc Drives (29 million bytes each) with control. Monthly rental and purchase prices are \$16,380 and \$599,280, respectively.

SMALL TAPE/DISC SYSTEM (USING OS/7): Consists of 196K Processor (with standard selector, multiplexer, storage protection, floating-point hardware, and 1401/1440/1460 emulation features), Console, 600-cpm Card Reader, 250-cpm Card Punch, 900/1100-lpm Printer, two Uniservo VI C (34KB) Tape Units with control, and two 8414 Disc Drives (29 million bytes each) with control. Monthly rental and purchase prices are \$17,840 and \$655,176, respectively.

MEDIUM TAPE/DISC SYSTEM (USING OS/7): Consists of 393K Processor (with two selectors, one multiplexer, storage protection, floating-point hardware, multiple channel switch, and 1401/1440/1460 emulation features), Console, 600-cpm Card Reader, 250-cpm Card Punch, 1200/1600-lpm Printer, four Uniservo 12 (68KB) Tape Units with control, and eight 8414 Disc Drives (29 million bytes each) with control. Monthly rental and purchase prices are \$27,155 and \$1,017,522, respectively.

LARGE 9700/9400 TAPE/DISC SYSTEM (USING OS/7): Consists of 786K Processor (with three selectors, one multiplexer with 31 subchannels, storage protection, floating-point hardware, three multiple channel switches, 1401/1440/1460 emulation, and two OSSF memory devices), Console, 1000-cpm Card Reader, 840/1000/2000-lpm Printer, eight Uniservo 20 (320KB) dual-access Tape Units with controllers, eight 8440 Disc Drives (110 million bytes each) with control; and a UNIVAC 9400 Subsystem consisting of a 32K processor, two UNISERVO VI C (34KB) Tape Units, two 8414 Disc Drives (29 million bytes each), two 900/1100-lpm Printers, two 1000-cpm Card Readers, and a 250-cpm card punch. Monthly rental and purchase prices are \$62,310 and \$2,364,721, respectively.

SOFTWARE AND SUPPORT: UNIVAC has not "unbundled" to date, so the equipment prices listed above include all of the UNIVAC software described in this report and all normal educational courses and professional assistance. UNIVAC Customer Support Facilities will provide conversion support, demonstrations, and benchmark processing for UNIVAC 9700 customers and prospects. This support, also, is included without additional charge.

CONTRACT TERMS: The standard UNIVAC use and service agreements allow unlimited use of the equipment (exclusive of the time required for remedial and preventive maintenance). There are no extra-use charges. The basic maintenance charge covers maintenance of the equipment for nine consecutive hours a day, Monday through Friday. Extended periods of maintenance are available at extra cost.

LONG-TERM LEASES: In addition to the basic 1-year agreement, UNIVAC offers an extended-term 5-year lease for 9700 systems at significantly lower monthly rates. Under the 5-year "level-payment" agreement, the monthly equipment charge is 80% of the 1-year rental rate shown in the accompanying price list. Under a 5-year "reducing-payment" agreement, the monthly charge is 90% of the 1-year rental rate during the first year, 85% the second year, 80% the third year, 75% the fourth year, and 70% the fifth year. ■

UNIVAC 9700 EQUIPMENT PRICES

		<u>Purchase Price</u>	<u>Monthly Maint.</u>	<u>Rental (1-year lease)*</u>
PROCESSOR AND MAIN STORAGE				
3024-00	9700 Processor (includes a Multiplexer Channel, a Selector Channel, 2 Interval Timers, and Storage Protection)	\$291,720	650	7,150
F1519-00	Expanded Interface; expands multiplexer to 15 subsystems (16 if F1518-00 is present)	5,508	15	135
F1518-00	Subchannel Expansion; expands multiplexer up to 31 subchannels	1,836	5	45
F1337-00	Selector Channel; 833KB; 8 subsystems (includes channel programming and storage protection; Selector Channels 3 and 4 require 1916-00 Channel Expansion Cabinet)	8,975	25	220
1916-00	Channel Expansion Cabinet (for third and fourth F1337-00 Selector Channels)	8,772	25	215
F1334-00	Floating-Point Control; four 64-bit registers and hardware instructions	1,836	10	45
F1335-00	Direct Control; interface for another 9000 Series processor plus 2 instructions for transfer of control information	3,672	10	90
F1591-00	1400 Emulation Control; for IBM 1401, 1440, and 1460 programs	4,080	0	100
4014-99	System Console; includes Uniscope 100 CRT; may be expanded by addition of one 0772-00 Printer and up to 6 multichannel switches	20,810	70	510
0772-00	Console Printer; 30 cps (required for OS/4)	10,200	45	250
2519-00	Multiple Channel Switch; 1 switch plus cabinetry for five F1541-00 expansion switches	6,936	20	170
F1541-00	MCS Expansion; one switch	3,264	10	80
F1001-00	Channel Adapter 9000 Series Subsystem; provides 9000 Series subsystem interface through respective multiplexer or selector channels	3,700	15	85
7018-00	Storage; 65,636 bytes	60,180	125	1,475
7018-99	Storage; 131,072 bytes	120,360	250	2,950
7018-98	Storage; 196,608 bytes	180,540	375	4,425
7018-97	Storage; 262,144 bytes	240,720	500	5,900
7018-96	Storage; 393,216 bytes	369,240	750	9,050
7018-95	Storage; 524,288 bytes	497,760	1,000	12,200
7018-94	Storage; 655,360 bytes	626,280	1,250	15,350
7018-93	Storage; 786,432 bytes	754,800	1,500	18,500
7018-92	Storage; 917,504 bytes	883,320	1,750	21,650
7018-91	Storage; 1,048,576 bytes	1,011,840	2,000	24,800
MASS STORAGE				
8405-99	OSSF; includes controller for 4 OSSF disc drives and one 3-million-byte head-per-track disc; 8.34-millisecond rotational delay	85,680	250	2,100
8405-04	OSSF Expansion; one 3-million-byte head-per-track disc; 8.34-millisecond rotational delay	26,520	100	650
8411-00	Disc Drive; 7.25 million bytes; 156KB/sec transfer rate	19,920	75	415
F1211-00	Disc Pack (for 8411 Disc Drives)	300	0	15
5024-00	Disc File Control (for up to 8 8411 drives)	20,010	80	460
F1043-00	Dual Channel Feature (for 5024-00); permits simultaneous access to the control from 2 selector channels	3,700	15	85
F1098-00	Record Overflow Feature (for 5024-00)	435	0	10
F1099-00	File Scan Feature (for 5024-00)	1,525	0	36
8414-92	Two 8414 Disc Drives; 58 million bytes; 312 KB/sec transfer rate	33,000	130	820
8414-94	Four 8414 Disc Drives; 116 million bytes; 312 KB/sec transfer rate	66,000	260	1,540
8414-96	Six 8414 Disc Drives; 174 million bytes; 312 KB/sec transfer rate	99,000	390	2,160
8414-98	Eight 8414 Disc Drives; 232 million bytes; 312KB/sec transfer rate	132,000	520	2,680
8414-85	Single 8414 Disc Drive (for configuration expansion); 29 million bytes; 312 KB/sec transfer rate	16,500	65	410
F1214-00	Disc Pack (for 8414 Disc Drives)	440	0	20
5024-02	Disc Control (for up to eight 8414 drives)	26,400	90	550
F1043-00	Dual Channel Feature (for 5024-02); permits access to the control from 2 selector channels	3,700	15	85
1371-99	Dual Access Feature (for 5024-02); permits simultaneous 2-channel access when used with 2 Disc Controls	2,160	5	45
1343-02	8411 Disc Capability (for 5024-02); allows attachment of 8411 drives to 5024 control in any combination with 8414 drives	1,920	10	40

* Rental prices do not include equipment maintenance.

UNIVAC 9700 EQUIPMENT PRICES

		<u>Purchase Price</u>	<u>Monthly Maint.</u>	<u>Rental (1-year lease)*</u>
MASS STORAGE (cont)				
8440-00	Disc Drive; 110 million bytes; 624 KB/sec transfer rate	\$ 27,840	145	580
F1482-00	Dual Access Feature (for 8440-00); permits simultaneous access to the drive from 2 controllers	2,160	5	45
F1220-00	Disc Pack; 110 million bytes (for 8440 Disc Drives)	1,100	0	0
5033-00	Disc Control (for up to eight 8440 drives); includes File Scan and Record Overflow	76,600	410	1,575
INPUT/OUTPUT UNITS				
0858-99	Uniservo VI C Subsystem; includes 9-track control for up to 8 units, Master Tape Unit, and 1 Slave Tape Unit	32,190	215	735
0858-10	Uniservo VI C Master Tape Unit; 9-track; 800 bpi; 34.16 KB/second	17,350	115	400
0858-14	Uniservo VI C Slave Tape Unit; 9-track; 800 bpi; 34.16 KB/second (3 slaves may be used with 1 master unit)	10,470	70	240
0861-00	Uniservo 12 Master Tape Unit; 9-track; 1600 bpi; 68.32 KB/second	20,015	100	460
F0934-99	Simultaneous Single-Density Feature (for 0861-00); requires 2 controls	3,265	15	75
F0934-01	Simultaneous Dual-Density Bi-Modal Feature (for 0861-00); requires F0934-99 and F0935-00 to give simultaneous access to dual density bi-modal (7- or 9-track) slaves attached to same master unit; control units each require F0826-00 and F1028-95	3,700	15	85
F0935-00	Dual Density Bi-Modal Feature (for 0861-00); control must have F0823-99; if 7-track slaves are present, control must also have F1028-95	2,175	10	50
0861-01	Uniservo 12 Slave Tape Unit; 9-track; 1600 bpi; 68.32 KB/second (3 slaves may be used with 1 master unit)	11,745	70	270
0861-04	Uniservo 12 Master Tape Unit; 7-track; 200, 556 or 800 bpi; 8.54, 23.74, or 34.16 KB/second	18,055	100	415
F0934-98	Simultaneous Single-Density Feature (for 0861-04); requires 2 control units which each must contain F0823-99	3,265	15	75
F1041-00	7- to 9-Track Conversion Feature (for 0861-04); converts to 0861-00	1,960	0	45
F1041-01	Simultaneous 7- to 9-Track Conversion Feature (for 0861-04 with F0934-98); converts to 0861-00 with F0934-99	1,960	0	45
0861-05	Uniservo 12 Slave Tape Unit; 7-track; 200, 556, or 800 bpi; 8.54, 23.74, or 34.16 KB/second (3 slaves may be used with 1 master unit)	10,440	70	240
F1042-00	7- to 9-Track Conversion Feature (for 0861-05); converts to 0861-01	1,305	0	30
5017-99	Uniservo 12 Non-Simultaneous Control (for up to 16 Uniservo 12 drives); 9-track; 1600 bpi	22,185	90	510
5017-00	Uniservo 12/16 Non-Simultaneous Control (for up to 16 Uniservo 12 and/or 16 drives); 9-track; 1600 bpi	23,925	100	550
F1131-99	Uniservo 16 Capability (for 5017-99)	1,740	10	40
F1029-99	Simultaneous Single-Density Access (for 5017-99); provides second control module	14,140	60	325
F1029-00	Simultaneous Single-Density Access (for 5017-00); provides second control module	15,880	70	365
F0823-99	7-Track NRZI (for 5017-00 or 5017-99)	4,785	15	110
F0826-00	9-Track NRZI (for 5017-00 or 5017-99)	4,785	15	110
F1028-95	Bi-Modal (7- or 9-Track) NRZI (for 5017-00 or 5017-99 with F0826-00)	3,480	10	80
F1028-96	Bi-Modal (7- or 9-Track) NRZI (for 1017-00 or 5017-99 with F0823-99)	3,480	10	80
F0825-00	Non-Simultaneous Dual Channel Feature (for 5017-00 or 5017-99)	3,700	15	85
8062-00	Uniservo 16 Magnetic Tape Unit; 9-track 1600 bpi; 192 KB/second (requires 5034-00 control)	31,755	110	730
0862-02	Uniservo 16 Magnetic Tape Unit; 7-track; 200, 556, or 800 bpi; 24, 66.72, or 96 KB/second (requires 5034-00 or 5017-00 control)	31,755	110	730
F0936-99	Simultaneous Feature (for 0862-00 or 0862-02); requires 2 controls	870	0	20
F0937-00	Dual-Density Feature (for 0862-00); control(s) must contain F0826-00 or F1028-96	2,175	0	50
F1040-00	7- to 9-Track Non-Simultaneous Conversion Feature (for 0862-02); converts to 0862-00	0	0	0
F1040-01	7- to 9-Track Simultaneous Conversion Feature (for 0862-02 with F0936-99); converts to 0862-00 with F0936-99	0	0	0

* Rental prices do not include equipment maintenance.

UNIVAC 9700 EQUIPMENT PRICES

		<u>Purchase Price</u>	<u>Monthly Maint.</u>	<u>Rental (1-year lease)*</u>
INPUT/OUTPUT UNITS (cont)				
5034-00	Uniservo 20 Magnetic Tape Unit; 9-track; 1600 bpi; 320 KB/second	\$ 41,280	140	860
F1510-00	Dual Access and Simultaneous Feature (for 5034-00); requires 2 controls	2,175	10	50
5034-00	Uniservo 20 Non-Simultaneous Control (for up to 16 Uniservo 12, 16, or 20 drives in any combination); 9-track; 1600 bpi (requires 2 controls for dual access)	43,200	90	900
F0823-98	7-Track NRZI (for 5034-00); adds bi-modal 7- or 9-track capability to control; may not be used with F0826-99	5,280	15	110
F0826-99	9-Track NRZI (for 5034-00); adds dual-density 800 or 1600 bpi to control; may not be used with F0823-98	6,240	20	130
F1028-97	Bi-Modal (7- or 9-track) NRZI (for 5034-00 with F0826-99)	4,320	10	90
F1028-98	Bi-Modal (7- or 9-track) NRZI (for 5034-00 with F0823-98)	5,280	15	110
0711-05	Card Reader and Control; 600 cpm	8,265	75	190
F0872-00	Short Card Feature; 51 Columns (for 0711-05)	1,425	10	37
F0872-01	Short Card Feature; 66 Columns (for 0711-05)	1,425	10	37
F1054-02	90-Column Read Feature (for 0711-05)	410	0	20
F1177-00	Validity Check Feature (for 0711-05)	720	0	15
0716-99	Card Reader and Control; 1000 cpm	13,680	90	285
F1487-00	Short Card Feature; 51 columns (for 0716-97)	1,425	10	37
F1487-01	Short Card Feature; 66 columns (for 0716-97)	1,425	10	37
F1488-00	Validity Check Feature (for 0716-97)	720	0	15
F1498-00	Alternate Stacker Fill Feature (for 0716-97)	480	0	10
F1530-00	Dual Translate; additional ASCII translator (for 0716-97)	960	5	20
0604-99	Card Punch and Control; 250 cpm	15,660	90	360
F0875-00	Read/Punch Feature (for 0604-99)	4,970	47	116
F1033-02	Paper Tape Reader; 300 char/sec	1,600	15	37
F1034-00	Reader Spooler (for F1033-02); 40 ips rewind	1,600	5	37
F1032-02	Paper Tape Punch; 110 char/sec	5,480	21	126
F1035-00	Punch Takeup Spooler (for F1032-02)	655	5	15
0920-02	Paper Tape Control (for F1033-02 & F1032-02)	7,540	26	173
0768-00	Printer and Control; 900/1100 lpm; 132 positions	40,675	315	935
0768-99	Printer and Control; 1200/1600 lpm; 132 positions	50,465	390	1,160
F1071-00	1600/1200-lpm Rate (converts 0768-00 to 0768-99)	9,790	75	225
0768-02	Printer and Control; 840/1000/2000 lpm	46,545	355	1,070
F1522-00	Print Code Expansion Feature (for 0768-02); provides 108-char. set	240	0	5
2703-00	Optical Document Reader; 300 dpm	42,000	175	875
F1108-00	600-dpm Speed Upgrade (for 2703-00)	10,560	30	220
F1163-00	Modulus 10 Check Digit (for 2703-00)	960	5	20
F1106-00	Mark Read - EBCDIC (for 2703-00)	7,920	35	165
F1106-01	Mark Read - ASCII (for 2703-00)	7,920	35	165
F1149-00	Punch Card Read Feature (for 2703-00); requires F1106-00 or -01	2,640	10	55
F1154-00	Validity Check Feature (for 2703-00); requires F1106-00 or -01	480	0	10
DATA COMMUNICATIONS SUBSYSTEMS				
F1395-00	Voice-Grade Communications Interface (for 9700 Processor); coordinates a BSC line and a 201A, 201B, 202C, or 202D type modem at up to 19,000 bits/second	720	5	15
F1395-01	Telpak Communications Interface (for 9700 Processor); coordinates a BSC line and a 301B, 303B, 303C, or 303D type modem	1,920	5	40
8577-02	DCS Cabinet; provides power supply and housing for up to 4 DCS-1 or -1C	2,772	5	58
F1000-00	Line Terminal Control-1 (for DCS-1); controls 1 duplex line	4,570	15	105
8575-00	Line Terminal Control-4 (for DCS-4); controls 4 duplex lines	10,500	42	242
8575-01	Line Terminal Control-16 (for DCS-16); controls 14 duplex lines	22,185	90	510

NOTE: Numerous line terminals, communications interfaces,
and optional features enable the above controls to accommodate
a wide range of communications facilities and equipment.

*Rental prices do not include equipment maintenance.

UNIVAC 9700

► **UTILITY ROUTINES:** An OS/4 or OS/7 Sort/Merge program capable of using disc and/or tape drives is available. It can sort fixed or variable-length records into either ascending or descending sequence, and includes provisions for the user's own coding. Disc-only sorts require enough disc capacity to hold all the records to be sorted plus sort control information. Tape-only sorts require 3 to 14 tape units, with no more than 6 tapes used for string collating. Tape/disc sorts use the disc to increase the length of the strings before collation is done on tape. The program's operation can be controlled by parameters entered either when the sort is generated or at run time. Up to 255 noncontiguous key fields can be specified, using shared input devices, if desired, and reserved output devices. The COBOL SORT verb generates a linkage to the Sort/Merge utility program.

A Linkage Editor combines object modules produced by the COBOL, FORTRAN, RPG, or Assembly language translators into "load modules" which are suitable for loading and execution under operating system control.

Library Service routines facilitate the creation and maintenance of various types of libraries on tape and disc for OS/4 or OS/7.

Other available utility programs for either the OS/4 or OS/7 operating system include data transcription routines, comprehensive data utilities to copy data from any input device to any output device, file maintenance routines, a dynamic (snapshot) dump, a terminal (postmortem) dump, and tape and disc listing programs.

For use under OS/4, UNIVAC offers a simulator for the UNIVAC 1050 and translators for IBM 1400 Series Autocoder and SPS and for IBM System/360 BAL.

Under OS/7, the IBM System/360 Assembler language is fully compatible with the UNIVAC 9700 Assembler. IBM 1401, 1440, and 1460 compatibility is handled through microprogrammed integrated emulation for certain time-consuming operations, supported by software subroutines for other emulated operations. More than one object program for the 1401, 1440, and 1460 can be run concurrently with other 9700 operations without reprogramming, using the 1400 Series disc, tape, and unit record files. UNIVAC claims 9700 emulation performance of 5.0 times native 1401 performance and 2.5 times native 1460 performance; these estimates are roughly similar to those claimed for the IBM System/360 Model 40 and the System/370 Model 145. UNIVAC 9700 software support required in conjunction with the special hardware compatibility features and microcode occupies from 45K to 60K bytes of main memory.

APPLICATION PROGRAMS: Programs announced to date include an advanced PERT Management Control System (MCS), LP 9700 (linear programming), UNIS (bill of materials, inventory control, planning and scheduling), PROFITS (on-line bank teller transaction processing), LINCO III (typesetting and line justification), and WIMS (Wholesale Inventory Management System). The 9700's announced compatibility with IBM System/360 DOS user programs will permit the use of most of the existing System/360 application programs, as described in the Management Summary.

PRICING

EQUIPMENT: All necessary control units and adapters are included in the indicated prices for the following typical configurations, and the quoted one-year rental prices include equipment maintenance. All figures reflect the price changes that became effective on February 1, 1972.

SMALL TAPE/DISC SYSTEM (USING OS/4): Consists of 131K Processor (with standard selector, multiplexer, and storage protection feature) Console, 600-cpm Card Reader, 250-cpm Card Punch, 900/1100-lpm Printer, two Uniservo VI C (34KB) Tape Units with control, and two 8414 Disc Drives (29 million bytes each) with control. Monthly rental and purchase prices are \$16,528 and \$601,690, respectively.

SMALL TAPE/DISC SYSTEM (USING OS/7): Consists of 196K Processor (with standard selector, multiplexer, storage protection, floating-point hardware, and 1401/1440/1460 emulation features), Console, 600-cpm Card Reader, 250-cpm Card Punch, 900/1100-lpm Printer, two Uniservo VI C (34KB) Tape Units with control, and two 8414 Disc Drives (29 million bytes each) with control. Monthly rental and purchase prices are \$17,997 and \$655,176, respectively.

MEDIUM TAPE/DISC SYSTEM (USING OS/7): Consists of 393K Processor (with two selectors, one multiplexer, storage protection, floating-point hardware, multiple channel switch, and 1401/1440/1460 emulation features), Console, 600-cpm Card Reader, 250-cpm Card Punch, 1200/1600-lpm Printer, four Uniservo 12 (68KB) Tape Units with control, and eight 8414 Disc Drives (29 million bytes each) with control. Monthly rental and purchase prices are \$27,357 and \$1,017,522, respectively.

LARGE 9700/9400 TAPE/DISC SYSTEM (USING OS/7): Consists of 786K Processor (with three selectors, one multiplexer with 31 subchannels, storage protection, floating-point hardware, three multiple channel switches, 1401/1440/1460 emulation, and two OSSF memory devices), Console, 1000-cpm Card Reader, 840/1000/2000-lpm Printer, eight Uniservo 20 (320KB) dual-access Tape Units with controllers, eight 8440 Disc Drives (110 million bytes each) with control; and a UNIVAC 9400 Subsystem consisting of a 32K processor, two UNISERVO VI C (34KB) Tape Units, two 8414 Disc Drives (29 million bytes each), two 900/1100-lpm Printers, two 1000-cpm Card Readers, and a 250-cpm card punch. Monthly rental and purchase prices are \$63,211 and \$2,357,601, respectively.

SOFTWARE AND SUPPORT: UNIVAC has not "unbundled" to date, so the equipment prices listed above include all of the UNIVAC software described in this report and all normal educational courses and professional assistance. UNIVAC Customer Support Facilities will provide conversion support, demonstrations, and benchmark processing for UNIVAC 9700 customers and prospects. This support, also, is included without additional charge.

CONTRACT TERMS: The standard UNIVAC use and service agreements allow unlimited use of the equipment (exclusive of the time required for remedial and preventive maintenance). There are no extra-use charges. The basic maintenance charge covers maintenance of the equipment for nine consecutive hours a day, Monday through Friday. Extended periods of maintenance are available at extra cost.

LONG-TERM LEASES: In addition to the basic 1-year agreement, UNIVAC offers an extended-term 5-year lease for 9700 systems at significantly lower monthly rates. Under the 5-year "level-payment" agreement, the monthly equipment charge is 80% of the 1-year rental rate shown in the accompanying price list. Under a 5-year "reducing-payment" agreement, the monthly charge is 90% of the 1-year rental rate during the first year, 85% the second year, 80% the third year, 75% the fourth year, and 70% the fifth year. ■

UNIVAC 9700 EQUIPMENT PRICES

		<u>Purchase Price</u>	<u>Monthly Maint.</u>	<u>Rental (1-year lease)*</u>
PROCESSOR AND MAIN STORAGE				
3024-00	9700 Processor (includes a Multiplexer Channel, a Selector Channel, 2 Interval Timers, and Storage Protection)	\$291,720	650	7,150
F1519-00	Expanded Interface; expands multiplexer to 15 subsystems (16 if F1518-00 is present)	5,508	15	135
F1518-00	Subchannel Expansion; expands multiplexer up to 31 subchannels	1,836	5	45
F1337-00	Selector Channel; 833KB; 8 subsystems (includes channel programming and storage protection; Selector Channels 3 and 4 require 1916-00 Channel Expansion Cabinet)	8,975	25	220
1916-00	Channel Expansion Cabinet (for third and fourth F1337-00 Selector Channels)	8,772	25	215
F1334-00	Floating-Point Control; four 64-bit registers and hardware instructions	1,836	10	45
F1335-00	Direct Control; interface for another 9000 Series processor plus 2 instructions for transfer of control information	3,672	10	90
F1591-00	1400 Emulation Control; for IBM 1401, 1440, and 1460 programs	4,080	0	100
4014-99	System Console; includes Uniscope 100 CRT; may be expanded by addition of one 0772-00 Printer and up to 6 multichannel switches	20,810	70	510
0772-00	Console Printer; 30 cps (required for OS/4)	10,200	45	250
2519-00	Multiple Channel Switch; 1 switch plus cabinetry for five F1541-00 expansion switches	6,936	20	170
F1541-00	MCS Expansion; one switch	3,264	10	80
F1001-00	Channel Adapter 9000 Series Subsystem; provides 9000 Series subsystem interface through respective multiplexer or selector channels	3,700	15	85
7018-00	Storage; 65,636 bytes	60,180	125	1,475
7018-99	Storage; 131,072 bytes	120,360	250	2,950
7018-98	Storage; 196,608 bytes	180,540	375	4,425
7018-97	Storage; 262,144 bytes	240,720	500	5,900
7018-96	Storage; 393,216 bytes	369,240	750	9,050
7018-95	Storage; 524,288 bytes	497,760	1,000	12,200
7018-94	Storage; 655,360 bytes	626,280	1,250	15,350
7018-93	Storage; 786,432 bytes	754,800	1,500	18,500
7018-92	Storage; 917,504 bytes	883,320	1,750	21,650
7018-91	Storage; 1,048,576 bytes	1,011,840	2,000	24,800
MASS STORAGE				
8405-99	OSSF; includes controller for 4 OSSF disc drives and one 3-million-byte head-per-track disc; 8.34-millisecond rotational delay	85,680	250	2,100
8405-04	OSSF Expansion; one 3-million-byte head-per-track disc; 8.34-millisecond rotational delay	26,520	100	650
8411-00	Disc Drive; 7.25 million bytes; 156KB/sec transfer rate	19,920	80	415
F1211-00	Disc Pack (for 8411 Disc Drives)	300	0	15
5024-00	Disc File Control (for up to 8 8411 drives)	20,010	85	460
F1043-00	Dual Channel Feature (for 5024-00); permits simultaneous access to the control from 2 selector channels	3,700	15	85
F1098-00	Record Overflow Feature (for 5024-00)	435	0	10
F1099-00	File Scan Feature (for 5024-00)	1,525	0	36
8414-92	Two 8414 Disc Drives; 58 million bytes; 312 KB/sec transfer rate	33,000	130	820
8414-94	Four 8414 Disc Drives; 116 million bytes; 312 KB/sec transfer rate	66,000	260	1,540
8414-96	Six 8414 Disc Drives; 174 million bytes; 312 KB/sec transfer rate	99,000	390	2,160
8414-98	Eight 8414 Disc Drives; 232 million bytes; 312KB/sec transfer rate	132,000	520	2,680
8414-85	Single 8414 Disc Drive (for configuration expansion); 29 million bytes; 312 KB/sec transfer rate	16,500	65	410
F1214-00	Disc Pack (for 8414 Disc Drives)	440	0	20
5024-02	Disc Control (for up to eight 8414 drives)	26,400	90	550
F1043-00	Dual Channel Feature (for 5024-02); permits access to the control from 2 selector channels	3,700	15	85
1371-99	Dual Access Feature (for 5024-02); permits simultaneous 2-channel access when used with 2 Disc Controls	2,160	5	45
1343-02	8411 Disc Capability (for 5024-02); allows attachment of 8411 drives to 5024 control in any combination with 8414 drives	1,920	10	40

* Rental prices do not include equipment maintenance.

UNIVAC 9700 EQUIPMENT PRICES

		<u>Purchase Price</u>	<u>Monthly Maint.</u>	<u>Rental (1-year lease)*</u>
MASS STORAGE (cont)				
8440-00	Disc Drive; 110 million bytes; 624 KB/sec transfer rate	\$ 27,840	145	609
F1482-00	Dual Access Feature (for 8440-00); permits simultaneous access to the drive from 2 controllers	2,160	5	45
F1220-00	Disc Pack; 110 million bytes (for 8440 Disc Drives)	1,100	0	0
5033-00	Disc Control (for up to eight 8440 drives); includes File Scan and Record Overflow	75,600	410	1,575
INPUT/OUTPUT UNITS				
0858-99	Uniservo VI C Subsystem; includes 9-track control for up to 8 units, Master Tape Unit, and 1 Slave Tape Unit	32,190	230	771
0858-10	Uniservo VI C Master Tape Unit; 9-track; 800 bpi; 34.16 KB/second	17,350	123	420
0858-14	Uniservo VI C Slave Tape Unit; 9-track; 800 bpi; 34.16 KB/second (3 slaves may be used with 1 master unit)	10,470	74	252
0861-00	Uniservo 12 Master Tape Unit; 9-track; 1600 bpi; 68.32 KB/second	20,015	107	482
F0934-99	Simultaneous Single-Density Feature (for 0861-00); requires 2 controls	3,265	16	78
F0934-01	Simultaneous Dual-Density Bi-Modal Feature (for 0861-00); requires F0934-99 and F0935-00 to give simultaneous access to dual density bi-modal (7- or 9-track) slaves attached to same master unit; control units each require F0826-00 and F1028-95	3,700	16	89
F0935-00	Dual Density Bi-Modal Feature (for 0861-00); control must have F0823-99; if 7-track slaves are present, control must also have F1028-95	2,175	10	52
0861-01	Uniservo 12 Slave Tape Unit; 9-track; 1600 bpi; 68.32 KB/second (3 slaves may be used with 1 master unit)	11,745	74	283
0861-04	Uniservo 12 Master Tape Unit; 7-track; 200, 556 or 800 bpi; 8.54, 23.74, or 34.16 KB/second	18,055	107	435
F0934-98	Simultaneous Single-Density Feature (for 0861-04); requires 2 control units which each must contain F0823-99	3,265	16	78
F1041-00	7- to 9-Track Conversion Feature (for 0861-04); converts to 0861-00	1,960	0	47
F1041-01	Simultaneous 7- to 9-Track Conversion Feature (for 0861-04 with F0934-98); converts to 0861-00 with F0934-99	1,960	0	47
0861-05	Uniservo 12 Slave Tape Unit; 7-track; 200, 556, or 800 bpi; 8.54, 23.74, or 34.16 KB/second (3 slaves may be used with 1 master unit)	10,440	74	252
F1042-00	7- to 9-Track Conversion Feature (for 0861-05); converts to 0861-01	1,305	0	31
5017-99	Uniservo 12 Non-Simultaneous Control (for up to 16 Uniservo 12 drives); 9-track; 1600 bpi	22,185	90	510
5017-00	Uniservo 12/16 Non-Simultaneous Control (for up to 16 Uniservo 12 and/or 16 drives); 9-track; 1600 bpi	23,925	100	550
F1131-99	Uniservo 16 Capability (for 5017-99)	1,740	10	40
F1029-99	Simultaneous Single-Density Access (for 5017-99); provides second control module	14,140	60	325
F1029-00	Simultaneous Single-Density Access (for 5017-00); provides second control module	15,880	70	365
F0823-99	7-Track NRZI (for 5017-00 or 5017-99)	4,785	15	110
F0826-00	9-Track NRZI (for 5017-00 or 5017-99)	4,785	15	110
F1028-95	Bi-Modal (7- or 9-Track) NRZI (for 5017-00 or 5017-99 with F0826-00)	3,480	10	80
F1028-96	Bi-Modal (7- or 9-Track) NRZI (for 1017-00 or 5017-99 with F0823-99)	3,480	10	80
F0825-00	Non-Simultaneous Dual Channel Feature (for 5017-00 or 5017-99)	3,700	15	85
0862-00	Uniservo 16 Magnetic Tape Unit; 9-track 1600 bpi; 192 KB/second (requires 5034-00 control)	31,755	110	730
0862-02	Uniservo 16 Magnetic Tape Unit; 7-track; 200, 556, or 800 bpi; 24, 66.72, or 96 KB/second (requires 5034-00 or 5017-00 control)	31,755	110	730
F0936-99	Simultaneous Feature (for 0862-00 or 0862-02); requires 2 controls	870	0	20
F0937-00	Dual-Density Feature (for 0862-00); control(s) must contain F0826-00 or F1028-96	2,175	0	50
F1040-00	7- to 9-Track Non-Simultaneous Conversion Feature (for 0862-02); converts to 0862-00	0	0	0
F1040-01	7- to 9-Track Simultaneous Conversion Feature (for 0862-02 with F0936-99); converts to 0862-00 with F0936-99	0	0	0

* Rental prices do not include equipment maintenance.

UNIVAC 9700 EQUIPMENT PRICES

		<u>Purchase Price</u>	<u>Monthly Maint.</u>	<u>Rental (1-year lease)*</u>
INPUT/OUTPUT UNITS (cont)				
0864-00	Uniservo 20 Magnetic Tape Unit; 9-track; 1600 bpi; 320 KB/second	\$ 38,400	140	800
F1510-00	Dual Access and Simultaneous Feature (for 0864-00); requires 2 controls	2,175	10	50
5034-00	Uniservo 20 Non-Simultaneous Control (for up to 16 Uniservo 12, 16, or 20 drives in any combination); 9-track; 1600 bpi (requires 2 controls for dual access)	43,200	90	900
F0823-98	7-Track NRZI (for 5034-00); adds bi-modal 7- or 9-track capability to control; may not be used with F0826-99	5,280	15	110
F0826-99	9-Track NRZI (for 5034-00); adds dual-density 800 or 1600 bpi to control; may not be used with F0823-98	6,240	20	130
F1028-97	Bi-Modal (7- or 9-track) NRZI (for 5034-00 with F0826-99)	4,320	10	90
F1028-98	Bi-Modal (7- or 9-track) NRZI (for 5034-00 with F0823-98)	5,280	15	110
0711-05	Card Reader and Control; 600 cpm	8,265	80	199
F0872-00	Short Card Feature; 51 Columns (for 0711-05)	1,425	10	38
F0872-01	Short Card Feature; 66 Columns (for 0711-05)	1,425	10	38
F1054-02	90-Column Read Feature (for 0711-05)	410	0	21
F1177-00	Validity Check Feature (for 0711-05)	720	0	15
0716-99	Card Reader and Control; 1000 cpm	13,680	90	299
F1487-00	Short Card Feature; 51 columns (for 0716-97)	1,425	10	38
F1487-01	Short Card Feature; 66 columns (for 0716-97)	1,425	10	38
F1488-00	Validity Check Feature (for 0716-97)	720	0	15
F1498-00	Alternate Stacker Fill Feature (for 0716-97)	480	0	10
F1530-00	Dual Translate; additional ASCII translator (for 0716-97)	960	5	21
0604-99	Card Punch and Control; 250 cpm	15,660	96	378
F0875-00	Read/Punch Feature (for 0604-99)	4,970	50	121
F1033-02	Paper Tape Reader; 300 char/sec	1,600	16	38
F1034-00	Reader Spooler (for F1033-02); 40 ips rewind	1,600	5	38
F1032-02	Paper Tape Punch; 110 char/sec	5,480	22	132
F1035-00	Punch Takeup Spooler (for F1032-02)	655	5	15
0920-02	Paper Tape Control (for F1033-02 & F1032-02)	7,540	27	181
0768-00	Printer and Control; 900/1100 lpm; 132 positions	40,675	337	981
0768-99	Printer and Control; 1200/1600 lpm; 132 positions	50,465	417	1,217
F1071-00	1600/1200-lpm Rate (converts 0768-00 to 0768-99)	9,790	80	236
0768-02	Printer and Control; 840/1000/2000 lpm	46,545	379	1,123
F1522-00	Print Code Expansion Feature (for 0768-02); provides 108-char. set	240	0	5
2703-00	Optical Document Reader; 300 dpm	42,000	187	918
F1108-00	600-dpm Speed Upgrade (for 2703-00)	10,560	32	231
F1163-00	Modulus 10 Check Digit (for 2703-00)	960	5	21
F1106-00	Mark Read - EBCDIC (for 2703-00)	7,920	37	173
F1106-01	Mark Read - ASCII (for 2703-00)	7,920	37	173
F1149-00	Punch Card Read Feature (for 2703-00); requires F1106-00 or -01	2,640	10	57
F1154-00	Validity Check Feature (for 2703-00); requires F1106-00 or -01	480	0	10
DATA COMMUNICATIONS SUBSYSTEMS				
F1395-00	Voice-Grade Communications Interface (for 9700 Processor); coordinates a BSC line and a 201A, 201B, 202C, or 202D type modem at up to 19,000 bits/second	720	5	15
F1395-01	Telpak Communications Interface (for 9700 Processor); coordinates a BSC line and a 301B, 303B, 303C, or 303D type modem	1,920	5	42
8577-02	DCS Cabinet; provides power supply and housing for up to 4 DCS-1 or -1C	2,772	5	60
F1000-00	Line Terminal Control-1 (for DCS-1); controls 1 duplex line	4,570	16	110
8575-00	Line Terminal Control-4 (for DCS-4); controls 4 duplex lines	10,500	44	254
8575-01	Line Terminal Control-16 (for DCS-16); controls 14 duplex lines	22,185	96	535

NOTE: Numerous line terminals, communications interfaces, and optional features enable the above controls to accommodate a wide range of communications facilities and equipment.

* Rental prices do not include equipment maintenance.